

A1 T3 PLUS TYPE HR IMPERMEABLE ROOF UNDERLAY

Protect A1 T3 Plus is a heavy-duty type HR roofing underlay, designed for all cold and warm pitched roofs in conjunction with the provision of ventilation at eaves and ridge, as well as the use of a well-sealed ceiling with a separate air and vapour control layer on the warm side of the insulation.

Now in its fourth generation, this four ply, high performance underlay is best in class, originally developed to overcome the disadvantages of traditional Type 1F and 5U felts as well as second generation plastic sheet materials.

With an increased product weight of 190gsm, the robustness of Protect A1 T3 Plus ensures it can provide a secondary line of defence against wind driven rain and snow with unrestricted wind uplift use across the UK and Ireland. Being entirely waterproof, it can be used to provide temporary protection during the period the roof covering is applied.*



Wind Uplift Resistance Zones 1-5 (345mm batten gauge)

NEW & IMPROVED PRODUCT WEIGHT

BENEFITS

- Regularly used for new build and re-roofing schemes.
- Completely air and watertight, achieving >2.0m hydrostatic head of water resistance.
- Has 'unrestricted' wind uplift resistance across the UK and Ireland at 345mm batten gauge, without the need for additional sealing tapes.
- Good nail tear and tensile strength.
- Easy to cut and handle, saving time on installation over traditional felts.
- Can be used as a temporary protection prior to installation of roof covering.*
- Does not generate nuisance noise under wind loading.
- Absorbent undersurface prevents condensate drip off.
- UV and heat resistant.

**For clarification on exposure times please contact Protect's Technical Team.*



protect

A1 T3 PLUS TYPE HR IMPERMEABLE ROOFING UNDERLAY

PRODUCT DESCRIPTION

Size

Roll width: 1.0m / 1.5m
 Roll length: 45m / 30m
 Roll total area: 45m²
 Roll weight: 8.55kg

Appearance

Embossed dark grey upper surface with grey lower surface. Printed with product branding for ease of identification.

Compatibility

As with all underlays, do not lay in direct contact with undried timber preservatives (whether water or solvent based). Protect OFV Eaves Skirt should be used at all gutter details.

Specification clause

Roofing underlay to be Protect A1 T3 Plus supplied by Protect Membranes, 2 Brooklands Road, Sale, Cheshire, M33 3SS. Tel: 0161 905 5700. Fax: 0161 905 2085. Email: info@protectmembranes.com

Underlay to be of four ply construction with a waterproof core that is laminated and protected between two layers of non-woven spunbond polypropylene, to achieve a hydrostatic head of water resistance of >2.0m. Undersurface to be absorbent to prevent condensate drip off. Resistance to wind uplift: unrestricted use in Zones 1-5 (at 345mm batten gauge). Underlay to be laid in accordance with BS 5534 and manufacturer's instructions.

Wind Uplift Resistance Map (345mm batten gauge)



PERFORMANCE

	MD	CD
Nail tear strength (N) to EN 12310-1 with mods	312	377
Unaged tensile strength (N/50mm) to EN 12311 with mods	417	321
Aged tensile strength (N/50mm) to EN 12311 with mods	392	327
Watertightness	Pass	Class W1 >2.0m hydrostatic head resistance
Weight	190gm ²	
Wind uplift resistance - Zones 1-5 (at 345mm batten gauge) and 600mm rafter centres		
Flexibility at low temperature	-40°C	

MD = machine direction (along roll), CD = cross direction (across roll).
 UV and heat ageing conditions: UVA lamps at 50°C for 336 hours followed by heat ageing at 70°C for 90 days.

Related products

Protect Fulmetal RediRoll: www.protectmembranes.com/rediroll
 Protect OFV Eaves Skirt: www.protectmembranes.com/eavesskirt
 Protect VC Foil Ultra Air and Vapour Control Layer membrane: www.protectmembranes.com/vcfoilultra

Stockist's stamp



PROTECT MEMBRANES

2 Brooklands Road, Sale, Cheshire M33 3SS

Tel: 0161 905 5700 Fax: 0161 905 2085

Email: info@protectmembranes.com Web: www.protectmembranes.com

Protect Membranes maintains a policy of continuous development and reserves the right to amend product specifications without notice.



A division of Building Product Design Ltd. Company Registration No: 3944123

